RESIDENTIAL GAS INFORMATION



- Gas installations should be done by a Journeyman Gasfitter; however, homeowners are allowed to install gas lines and appliances if they own and reside in the home.
- Air tests are witnessed by the gas supplier or by means set out by the local authority, the Safety Codes Officer does not witness an air test.
- When using corrugated stainless-steel tubing (CSST), you MUST use the brand's certified installation and sizing instructions. CSST also requires you to have a ticket to install before you run it in your home.
- Majority of venting for the energy efficient appliances are to be done to the manufacturer's certified instructions.
- Secondary lines to buried 15 to 24 inches below grade with a tracer wire. They can be deeper when required for added protection. For example, a farm field where equipment is working up the land.
- > All underground piping shall rise above ground before entering a building.
- > All propane tank sets and installations require a permit.

Canadian Standards Association

Table A.2

Maximum capacity of natural gas in thousands of Btuh for Schedule 40 pipe and plastic pipe, including fittings, for pressures of 7 in w.c. up to 14 in w.c. based on a pressure drop of 1 in w.c. (See Clauses 6.3.2, 6.3.4, 6.3.5, A.2.3, A.2.4, A.2.6, A.3.5, E.1.2, and E.2.2.)

Length of pipe, ft	Pipe size (NPS)								
	1/2	3/4	1	1-1/4	1.1/2	2	2-1/2	3	4
10	227	474	894	1 835	2 749	5 295	8 439	14 919	30 425
20	156	326	614	1 261	1 890	3 6 3 9	5 800	10 253	20 914
30	125	262	493	1 013	1 517	2 922	4 658	8 234	16 795
40	107	224	422	867	1 299	2 501	3 986	7 047	14 37
.50	95	199	374	768	1 151	2 217	3 5 3 3	6 246	12 739
60	86	180	339	696	1 043	2 008	3 201	5 659	11 543
70	79	166	312	640	959	1 848	2 945	5 206	10 619
80	74	154	290	596	893	1 719	2 740	4 843	9 87
90	69	145	272	559	837	1 613	2 571	4 544	9 266
100	65	137	257	528	791	1.524	2 428	4 293	8 75
125	58	121	228	468	701	1 150	2 152	3 805	7 76
150	52	110	207	424	635	1 223	1 950	3 447	7 03
175	48	101	190	390	584	1 1 26	1 794	3 1 7 1	6 46
200	45	94	177	363	544	1 047	1 669	2 950	6 01
250	40	83	157	322	482	928	1 479	2.615	5 33
500	36	75	142	291	437	841	1 340	2 369	4 83.
350	33	69	131	268	402	774	1 233	2 180	4 4 4
400	31	64	121	249	374	720	1147	2 0 2 8	413
450	29	61	114	234	351	675	1 076	1 903	3 88
500	27	57	108	221	331	638	1 017	1 797	3 66
600	25	52	98	200	300	578	921	1 628	3 32
700	23	48	90	184	276	532	847	1 498	3 05
800	21	44	83	171	257	495	788	1 394	2 84
900	20	42	78	161	241	464	740	1 308	2 66
000	19	39	74	152	228	438	699	1 235	2 515
200	17	36	67	138	206	397	633	1 119	2 28
400	16	33	62	127	190	365	582	1 030	2 100
600	15	30	57	118	177	340	542	958	1 95
1 800	14	29	54	111	166	319	508	899	1 833
2 000	13	27	. 51	104	156	301	480	849	1 732

(a) Imperial


(Continued)

January 2010

113

April 16, 2020

23



1. A MECRANICAL (FAN ASSISTED) AIR INTAKE.